



Card Reader

RD3001

Spec: single-head, dual-slot single read

Key Features

High-speed stable transfer

Direct Type-C connection

Technical Specifications

Upstream Port	Type-C3.0
Function	TF
Material	ABS
Dimensions / Weight	43.5×20×10mm / 5.2g
Color	Black
Operating System	Windows, macOS, iOS, Android, HarmonyOS, Linux
Operating Temperature	0°C - 70°C; Storage: -20°C - 80°C
Warranty	3 Years

Typical Applications

Photo / video import

Drone data export

Phone / tablet expansion

Surveillance playback

OEM / ODM Capabilities

Customization

- Laser / silk-screen logo
- Custom housing color & material
- Capacity & firmware options
- Custom color box / inner packing

Quality Assurance

- ISO 9001 / 14001 / 45001
- IQC and in-process inspection
- 100% functional test before shipment
- Replacement within warranty

Delivery

- MOQ from 500 pcs
- Lead time 30 days
- Sampling / small batch supported
- Drop-shipping & bulk packing

CE · FCC · RoHS

Certified since 2024; renewed in 2026
Copies available on request

Product View



Product Photo

Measured Performance

CrystalDiskMark 8.0.0 x64 [Admin]			
文件(F) 设置(S) 显示状态 主题(T) 帮助(H) 语言(L)(Language)			
All	5	1GiB	H: 0% (0/58GiB)
			MB/s
	Read (MB/s)		Write (MB/s)
SEQ1M Q8T1	203.24	141.36	
SEQ128K Q32T1	204.41	141.00	
RND4K Q32T1	8.44	7.80	
RND4K Q1T1	8.40	7.80	

Performance Test Screenshot